



Argo 6x6 Frontier EFI



Argo 6x6 750 HDi



Argo 8x8 Frontier EFI

VEHICLE	6 X 6 FRONTIER EFI	6 X 6 750 HDI	8 X 8 FRONTIER EFI
Engine	Kohler Command Pro		
Engine Warranty	3 year		
Type	4 cycle OHV V-Twin gasoline engine, electronic ignition, full pressure lubrication and oil filter.		
Horsepower	19 or 23 ¹⁰	23	
Displacement	694cc or 747cc ¹⁰	747cc	
Cooling	Air Cooled		
Starting	Electric		
Brakes	Hydraulic		
Steering	One-piece, ergonomic handlebar Steering control features hand brake. For safety and ease of handling, the ARGO steering transmission provides continuous torque to all axles.		
Controls	Right-hand twist grip throttle. Light switch and ignition switch.		
Clutch	Belt-driven, Continuously Variable Transmission (CVT) maximizes engine power to the transmission.		
Transmission	Planetary ⁸	ADMIRAL ⁸	Planetary ⁸
Drive System	Roller chains drive machined sprockets that are spline-fit onto 1 1/4" diameter axles and are protected with triple-sealed greaseable bearings.		
Frame	Formed steel channel construction, welded for high strength and durability. Polyester powder-coated for lasting protection.		
Body	Vacuum formed High Molecular Weight Polyethylene		
Full Skid Plate	Optional	Standard	Optional
Load Capacity ¹	On Land	700 lb. (318 kg) total ²	
	Rear Compartment	140 lb. (64 kg) max.	
	On Water	500 lb. (227 kg) total	
Towing Capacity ³	1,200 lb. (544 kg)	1,400 lb. (635 kg)	
Seating Capacity ⁴	On Land	4 persons	
	On Water	2 persons	
Fuel Capacity	7.1 US gallons (27 litres) See-through polyethylene fuel tank. 8 hrs. operation ⁵		
Speed ⁶	On Land	22 mph (35 km per hour)	
	On Water ⁷	3 mph (5 km per hour)	
Shipping Weight	880 lb. (399 kg)	950 lb. (431 kg)	1,090 lb. (494 kg)
Dimensions (L X W X H)	(inch)	95 x 58 x 45.8	
	(mm)	2,413 x 1,473 x 1,163	
Axle Bearing Extensions	Front - Optional	Front - Standard	
	Rear - Optional	Rear - Standard	Rear - Optional
Instrumentation	LCD Digital Gauge Cluster: Speedometer, Odometer, Voltmeter, Hour Meter, Tachometer, Low Oil Pressure and Parking Brake Reminder Lights, Check Engine Light.		
Tires	ARGO AT189 24x10.00-8NHS		
Ground Pressure	1.7 psi (13.5 kPa) using tires 0.67 psi (4.6 kPa) using tracks		
Ground Clearance	Tires	9.5" (240 mm)	
	Tracks	10.5" (265 mm)	
Operating Conditions	All weather, all terrain, -40°F to +104°F (-40°C to +40°C)		

1 Capacity includes occupants, cargo, outboard motor and fuel, and installed accessories.

Max. outboard motor size 7.4 kW (9.9 hp).

2 Total payload is 700 lb. (318 kg) with max. 140 lb. (64 kg) allocated to rear compartment.

3 Towing capacity is approximate and depends on type of surface, load on vehicle as well as incline.

Max Hitch Tongue Load (when equipped with hitch) 100 lb. (45 kg) for all models

4 Subject to rear compartment load capacity limitations.

5 Fuel consumption depends on load and operating conditions.

6 All speeds are approximate and depend on conditions.

7 Always wear approved Personal Floatation Device (PFD) when operating in water or on ice.

8 ADMIRAL triple differential steering transmission with dedicated Hi and Low selector; Forward, Neutral, Reverse.


9 Planetary differential transmission with High and Low range; Forward, Neutral, Reverse.

10 Dependent on engine selection.

AVAILABLE ARGO COLORS

Colors are reproduced with great care, but may vary slightly from actual ARGO vehicle colors.

MOSSY OAK



COLOR OPTIONS FOR ALL STEEL PARTS

Ultra Chrome and other colors or custom coatings available on request.



220 Bergey Court
New Hamburg, ON
Canada N3A 2J5
Toll Free: 1-877-274-6288
Tel: (519) 662-4000
Fax: (519) 662-2421
www.ARGOutv.com

Safety!
...always in Season!

treadlightly!
ON LAND AND WATER

Proud to be located in
Canada's
Technology
Triangle

Appearance and specifications subject to change without notice. For safety, always wear approved helmets and eye protection. When operating in water, always wear approved Personal Floatation Devices. Always remain seated while in the ARGO. Optional accessories shown.