

# AURORA PRO 950 XT SAR 8X8



## HIGHLIGHTS

### Engine:

- VX EFI Fan-Cooled V-Twin with Hood Fan

### Drivetrain:

- Automatic Admiral Transmission
- Triple Differential
- H/L/N/R
- Instant Torque Clutches

### Steering:

- APS (Argo Progressive Steering)

### Seating Capacity:

- 4 People

### Tires/Wheels:

- XT117 Tire
- 25x12-9
- Steel Beadlock Wheels

### Key Features:

- Heavy-Duty Front Brushguard
- 3,500 lb. Winch
- HDPE Amphibious Body
- Split Seats
- Stretcher Mount
- Brake Cooling Fan
- Automatic Chain Lubrication System
- Easy-Access Grease System
- 2" Receiver Hitch
- 1,800 lb. Towing Capacity
- Certified ROPS

RED  
**1** YEAR | **3** YEAR  
BUMPER TO BUMPER | POWERTRAIN  
**COMMERCIAL WARRANTY**

# AURORA PRO 950 XT SAR 8X8



## ENGINE

Cylinder	V-Twin
Fuel System	EFI
Cooling	Fan Cooled
Alternator Output (max)	50 AMPS

## DRIVETRAIN

Transmission Type	Admiral w/APS
Drive Belt	Heavy Duty
Service Brakes	Hydraulic
Steering Brakes	Hydraulic
Brake Cooling Kit	Standard
Auto Chain Lubrication	Standard
Speed on Land	25 mph (40 Km/h)
Speed on Water	Water Fording

## DIMENSIONS/WEIGHT

Length	126 in (3,200 mm)
Width	60 in (1,524 mm)
Height	77 in (1,956 mm)
Weight	1,886 lb. (654 kg)
Load Capacity – Land	654 lb. (297 kg)
Load Capacity – Water	454 lb. (206 kg)
Towing Capacity	1,800 lb. (816 kg)
Fuel Capacity	8.5 gal (32.2 L)
Seating Capacity – Land	4
Seating Capacity – Water	2

## TIRES & WHEELS

ARGO Tires	ARGO XT117 25X12-9
Wheel	Steel Beadlock
Ground Clearance – Tires	10 in (254 mm)
Ground Clearance – Tracks	11 in (279 mm)
Ground Pressure - Tracks	0.88 psi (6.1 kPa)

## FEATURES

Front Rack	Accessory
Brushguard	Standard
Winch	3,500 lb.
Full Skid Plate	Standard
Bilge Pump	Standard
Entry Step	Accessory
Axle Bearing Extensions	Standard
Easy Access Grease System	Standard
ROPS	Standard
Rear Mesh	N/A
Roof	Accessory
Stretcher Frame	Accessory
Cargo Box	N/A

## COLOR

Red

